

SELF/5000_{LE}

Compact, engaging and scalable all-in-one payment solution for your self-service business



Accept all payment methods including magstripe, EMV and NFC/Contactless and QR codes



Easily integrate cashless payment in self-service business like vending or indoor kiosks



Simplify solution integration, operation and scalability



Comply with the EVA EPS standard



Self/5000 LE, an all-in-one device designed to grow your self-service business.

All methods of payment accepted including QR-code based payment

Ruggedized:

- Designed for intensive use cases: IK09
- Indoor
- Outdoor within the limits of IP44

Easy integration:

- Can be integrated into a kiosk from the front or from the rear
- Compliant with EVA EPS (Standard Door Module) standard, the Self/5000 can easily replace the older solutions

Low Energy platform, showcasing faster boot times and a deep sleep mode for optimized performance

High level of security with PCI PTS certification

Modularity:

- Add-on boxes to build the desired configurations (Power, MDB, EXE, Wireless)
- Upgradeable in the field

Ergonomic interface:

- Easy-to-use customer interface thanks to a simple UI
- Color and capacitive touch screen

Supported by the suite of services provided by Ingenico 360 platform from device management to Managed Services



Specifications

Processor/OS	• Low energy platform • Telium TETRA	✓ ✓
Memory	• 512 MB Flash, 512 MB RAM • MicroSD up to 32GB	✓ ✓
Contactless reader	• EMV Contactless L1 2.6 certified / Support ISO 14443	✓
Contact reader	• Hybrid card reader with shutter • RGB LEDs in reader's entry mouth • Smart card – EMV L1 – 500k reads lifespan • MSR ISO 1/2/3 – 500k reads lifespan	✓ ✓ ✓ ✓
SAM	• 2xSAM ID-000	✓
Display	• 3.26" color QVGA (240x320)	✓
Touchscreen	• Capacitive - 6mm glass thickness	✓
Keypad	• Virtual keyboard on screen	✓
Audio	• Buzzer Monotone • Wav sound (thru external speaker)	✓
Camera	• 2MP – fixed focal (Honeywell library embedded)	Option
Terminal connections	• 1 x USB Slave • 2 x USB Host • 2 x RS232 • 1 x connector for external loudspeaker • 1 x MDB Master + 1 x MDB Slave	✓ ✓ ✓ ✓ Option
Terminal connectivity	• Ethernet 10/100, 1 x RJ45 LAN port • 4G	✓ ✓
Security	• PCI PTS 6 certified • PIN on Glass certified	✓ ✓
IP	• IP 44	✓
IK	• IK 09	✓
Power supply	• 9-16 V DC (light sleep mode) • 10-45V DC with optional Add-on box • Deep sleep mode for low consumption	✓ Option ✓
Terminal size	• EVA EPS – Standard Door Module • 85 (W) x 107.2 (H) x 109.6 (D) mm (3.3x4.2x4.3")	✓ ✓
Weight	• 620 g (22 oz)	✓
Environment	• -20°C to +70°C (-4°F to 158°F) – Operating • -20°C to +70°C (-4°F to 158°F) – Storage • 95% non-condensing at +55°C (131°F)	✓ ✓ ✓
Mounting in the kiosk	• From outside without EVA plate • From inside with EVA plate	✓ ✓
Accessory	• Adapter cable for standard 12V PSU • EVA EPS mounting steel plate • USB cables, serial cables... • PSU 12V DC...	✓ ✓ Option Option
Add-on boxes	• POWER add-on box (slot#1) • MDB or EXE add-on box (slot#2) • 4G add-on box (slot#2)	Option Option Option

